

**HIGH STRENGTH
FLEXIBLE MEMBRANE****SEAMLESS WATERPROOF
SURFACE PROTECTION****COMPLETE SHOWER-SAFE
PROTECTION SYSTEM****Description:**

BONDMASTER TANKING KIT is a waterproof barrier system designed to protect water sensitive structures and surfaces in tiled areas where regular and frequent exposure to damp conditions is expected, such as showers, bathrooms, wet-rooms and kitchen utility areas. This multi-component system consists of a surface primer to ensure good adhesion to the substrate; a grey flexible waterproof coating to prevent the passage of moisture and super strong polyester matting to reinforce seams in joints around wall floor junctions and where piping enters and exits the wet zone. This provides a seamless, durable protective membrane to inhibit the passage of moisture from within the tiled area through to surfaces and structures which may be sensitive to the effects of prolonged water migration, such as plaster, render, plasterboards, tile backer boards, timber, suspended floors and plywood overlays. The BONDMASTER TANKING KIT barrier system is flexible enough to accommodate any slight movement or vibration which may be expected under normal conditions of use in and around well constructed, structurally stable floors, walls, showers and utility fittings.

Surface Preparation:

New concrete or plaster surfaces should be allowed at least 6 weeks to adequately dry out before BONDMASTER TANKING KIT is applied. Timber and boarded structures must be rigidly braced and sufficiently constructed to withstand anticipated loading without flexing, deformation or any movement around joints and seams. Timber floors and walls must also have sufficient ventilation from behind and below to avoid interstitial condensation. Surfaces to be coated must be clean, dry and free from oil, grease and any other contaminants. Seal all gaps, joints and cracks with MULTI-PURPOSE SILICONE SEALANT or in wider gaps a suitable repair compound and then allow this to fully cure before proceeding. Ensure the finished surface is sufficiently level and even to accommodate a flat regular tiled finish and any floor surface inclines running to a drain point are true and ensure water flows off in the correct direction. When the wet-zone area is structurally sound, prime all surfaces (floors and walls) with a single coat of BONDMASTER TILERS PRIMER and then allow this to dry.

Application Method:

When the surface is adequately prepared and the primer coat has dried, BONDMASTER TANKING KIT waterproof coating should first be brush or roller applied generously around all horizontal and vertical joints, corners, cracks and seams in and around the backing surfaces and at the joints surrounding pipe penetrations and drainage gullies. Whilst this coating is still wet, press in the polyester tape along and bridged over the seam line around all surface joints and fittings and at the junction between different surface materials. When all the joints and edge seams are sufficiently sealed with polyester tape apply a second coat of BONDMASTER TANKING KIT to seal in the polyester tape where

necessary. As the taped seams dry out use a brush or roller to apply an even and consistent coating over all exposed wall surfaces including the taped & sealed joints. Once the wall area is treated, on any floor areas exposed to the most frequent wetting and trafficking i.e. below the shower point, apply a coat of BONDMASTER TANKING KIT across the floor and then cut to size (if necessary) and evenly press out the square metre of polyester matting, leaving no creases or wrinkles, whilst ensuring it accurately accommodates any drain points. When the polyester matting has dried into place, generously apply a second coat BONDMASTER TANKING KIT waterproof coating over all previously laid polyester covered based and then out across all exposed and previously taped wall and floor joints within the defined wet-zone area. Allow 24 hours for BONDMASTER TANKING KIT waterproof coating to dry out and re-apply a fresh coat over any voids or areas where the first application has failed to achieve sufficient coverage

Fixing on BONDMASTER TANKING KIT:

Walls sealed with BONDMASTER TANKING KIT should be treated as impermeable surfaces and joints around tiles fixed using ready mixed waterproof wall tile adhesives such as BONDMASTER WATERPROOF TILE ADHESIVE should not be grouted until up to 7 days after fixing. Porcelain or large format tiles (greater than 300mm x 300mm) should be fixed to walls using a polymer modified cement-based adhesive such as BONDMASTER RAPID SET FLEXIBLE or VITRIFIED FLEXIBLE. Floor surfaces in wet zones sealed with BONDMASTER TANKING KIT should always be tiled over using the same polymer modified cement-based C2 adhesives as recommended above for large format tiles. Under tile heating mats can fixed to the BONDMASTER TANKING KIT membrane and then be tiled over using BONDMASTER RAPID SET FLEXIBLE or VITRIFIED FLEXIBLE polymer modified cement-based adhesives. BONDMASTER TANKING KIT should not be left as a final exposed wearing surface, nor should it be used in external locations or where the tiled area is intended for permanent & continuous water immersion.

Coverage:

Depends on the surface texture and porosity, however on a typical smooth, even surface BONDMASTER TANKING KIT waterproof coating will cover at about 2 - 3 square metres per litre. The pack as supplied is sufficient to cover 5 square metres which is equivalent to a single domestic shower cubicle.

Storage & Packaging:

BONDMASTER TANKING KIT is supplied with 1 litre of BONDMASTER TILERS PRIMER; 2.5 litres of waterproof coating; 10 linear metres of 100mm wide polyester tape and 1 square metre of polyester matting. Should more technical information be required, contact the Technical helpline

The information provided by this Technical data sheet is given in good faith and is to the best of our current knowledge true and accurate. However it is given without guarantee, as conditions of use and workmanship involved are both beyond our control. All information supplied is subject to the company's terms and conditions of sale, copies of which are available on request.

McLOUGHLINS  Ltd
UNIT 5 Northern Cross Business Park, North Road, Finglas, Dublin 11, Ireland Tel: 3531 8239 200; Fax 3531 8239 222
www.mcloughlinsrs.ie

BONDMASTER
BONDMASTER