
## **TECHNICAL DATA SHEET**

## VM40B Deck Mounted Thermostatic Bath Shower Mixer Valve

Barcode	7081243314287
Product Code	VM40B
Construction	Brass Body (CuZn38Pb18)
Finishes	Chrome plated to BS EN 248
Product Type	Contemporary
Water Pressure	Min. 0.2 bar, Max. 6.0 bar
Plumbing Systems	Suitable for all plumbing systems, preferably balanced.Min. supply pressure differential requirement is 5:1
Standards	Complies with BSEN 1111
Certification	Manufactured to comply with WRAS, TMV2
Cartridge	Thermostatic; Ceramic disc cartridge
Fitting	Brass ¾" BSP deck mounted pillars
Check valve	0.5-10 gpm
Packaging	41.5x35x41cm/carton(10pcs), Box size: 33.5x20x8, Weight: 2.54kg/pcs
Guarantee	10 years against manufacturing faults (excluding serviceable parts).
Additional Information	<ol> <li>Temperature: Pre-set 38°C, with push button override to 48°C.</li> <li>Automatic shut off in the event of hot or cold water supply failure.</li> </ol>





Flow Rates (Litres per minute)

System Pressure	0.1 Bar	0.2 Bar	0.3 Bar	0.5 Bar	1.0 Bar	1.5 Bar	2.0 Bar	3.0 Bar	4.0 Bar	5.0 Bar
VM40B	6.0	6.8		8.3	12.0	15.0	18.5	22.5	-	-

The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. We pursue a policy of continuing improvement in design and performance of our products and so reserve the right to change specifications without prior notice.

